

# TECHNICAL DATASHEET

**DET**

Sept. 2025

Cleaning and defluxing solvent

## PRODUCT DESCRIPTION

Label Remover **DET** has been specially formulated by our laboratory to be a quick and efficient removal of paper based pressure sensitive adhesive labels. DET is 100% Ozone Friendly.

DET has a very large range of application and this product is compatible with a large range of plastics materials.

## FEATURES

- Allows label to be simply peeled off without leaving adhesive residue or scratching surface.
- Compatible with most plastics, rubbers, elastomers, and surface coatings when used as directed. Test sensitive plastics on a small area first, and do not use on polystyrene.
- Non-CFC, and non-halogenated solvent.
- DET is a dry solvent, no greasy residues after evaporating.
- Available in cans and bulks.

## PRODUCT USE

Spray or wipe on, leave in contact for 5 minutes and then peel off label. Wipe surface clean.

DET contains flammable solvents, so it must not be sprayed directly on turning on electrical equipment or near a heat source.

## PROPERTIES

Specific Gravity @ 20°C:	0.79
Inhalation Toxicity:	300 ppm
Flash Point:	0°C
Residue on Evaporation:	<1ppm
Evaporation Rate:	16 (with ether as 1)

## PACKAGING

400ml Aerosol with Brush  
1 Litre Bulk  
5 Litre Bulk  
30 Litre Bulk

## ORDER CODE

DET 400 B  
DET 01L  
DET 05L  
DET 30L

### *ABchimie*

1230 Route de La Porte – ZA La Rivoire – 38630 Corbelin – France  
Tel : +33 (0)4 74 83 12 19 – Fax +33 (0)4 74 83 68 62

**TDS DET**  
[info@abchimie.com](mailto:info@abchimie.com)  
[www.abchimie.com](http://www.abchimie.com)



The DET is compliance with REACH and RoHS regulations. If you want a certificate, please contact us ([info@abchimie.com](mailto:info@abchimie.com)). Please refer to the separate Health & Safety Data Sheet for further details.

### **STORAGE AND DATE OF USE:**

**Storage temperature:** 5 to 30°C

A temporary lower or higher temperature during few days (transport) doesn't distort varnish properties.

**Date by use:** 24 months after the date of manufacturing (18 months in spray)

*All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. ABchimie cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.*